

T1072-3W

For Lights & Motors

This easy-to-install switch handles motors, all types of lighting, and features both the flexibility of 7-day programming and the convenience of automatic sunset/sunrise activation

MODEL & RATINGS

T1072-3W 1800 W max. 120 V, 60 Hz 15 A (I,R) 12 A tungsten 1 HP



PROGRAMMABLE

SPECIFICATIONS

PROGRAMMING

7-day programming, up to 42 events
Solar timetable can be used simultaneously with daily programs*

OPERATING MODES

Manual (conventional on/off switch)
Automatic
Random

CONNECTION

Single pole 3 wire (line, load, neutral) or
Multiswitch (3-way) 4 wire (line, load, 3-way, neutral)

DIMENSIONS (H•W•D)

68 x 43 x 43 mm / 2.7 x 1.7 x 1.7 inches

FEATURES

Sleek design mounts flush with wallplate

Works with motors and all types of lighting
(compatible with electronic ballasts, compact fluorescent lights and tungsten lighting up to 12 A)

Large white backlit display with a night light mode option for easy reading in dark areas

Confirmation LED for at-a-glance load status (on or off)

Random mode activates lights randomly to simulate a presence when away from home

Easy intuitive 3-button interface – no door to open


Automatic daylight savings – no need to reprogram

Hidden lock feature prevents tampering without requiring costly security cover

PROGRAMMING

Up to 21 programs (21 on/off times) per week. A program can apply to a single day or repeat every day. Sunset/sunrise times are calculated automatically every day. *For each day of the week, the user can choose: sunset/sunrise programming or their own on/off time, or one of each (e.g. sunset and midnight).

INSTALLATION



T1072-3W

PRODUCT



SPECIFICATIONS

WEIGHT

Clamshell	0.282 kg
Inner box	1.472 kg
Master box	6.956 kg

DIMENSIONS

	H	W	D
Clamshell	8.75 in.	6.25 in.	2.25 in.
Inner box	9.8 in.	8.7 in.	14.6 in.
Master box	21 in.	15.2 in.	18.3 in.

INNER / MASTER QUANTITY

Inner box	5 units
Master box	20 units

